

## FAXE Wooden Floor Oil

Series: 0276

Oiling of untreated and lye-treated wood.

FAXE Wooden Floor Oil is for application on untreated or lye treated solid wood and parquet flooring in living areas. It makes the wood dirt resistant and hard-wearing. FAXE Wooden Floor Oil dries quickly and is also suitable for professional use. It can be applied to small areas by hand or to large areas using a machine.

### Preparation:

The wood must be sanded down, with a fine grain pad or disc, clean, grease-free and dry. Pre-cleansing with FAXE Intensive Cleaner improves the quality of the surface and intensifies the colour effect. Application temperature: min. 18°C. Treat large areas in sections of approx. 15 m<sup>2</sup>.

Empty the complete contents of the container into a plastic vessel, stir thoroughly before and during use. Several containers containing identical products should be mixed together. The finished result depends, amongst other things, on the preparatory treatment, structure and natural colour of the substrate. For this reason, try out first on a sample area.

### Application:

1. Apply the oil evenly using a roller. Allow to soak in for 10 – 15 minutes, the wood should appear wet and shiny. Apply more oil, if dry areas appear.
2. Skim off excess oil with the rubber squeegee. Mix the excess oil with fresh oil and use for the next section.
3. Consolidate and smooth the skimmed surface with the massage pad and wipe any remaining oil off with an absorbent cloth or woolpad.
4. For a perfect finish, polish the surface the following day using a polishing pad and a little oil (5-10 ml/m<sup>2</sup>).
5. Leave to dry for several hours and then cover areas that need to be walked on with cloths or corrugated cardboard. The floor must be protected against moisture until the oil has hardened out.

### After Care:

Dust and loose dirt can be removed with a brush or vacuum cleaner. We recommend FAXE Wooden Floor Soap or Faxe Oilsoap for cleaning. Colour and sheen can be enhanced by using FAXE Active Care. To renovate, clean the surface with FAXE Intensive Cleaner and then apply a coat of FAXE Maintenance Oil.

### Technical data:

Cleaning: Clean tools with Faxe Oil Thinner

Storage: Dry and cool.



**Components:**

Refined vegetable oils, low aromatic naphtha, drying agents, titanium white (in white version).

VOC: 2004/42/IIA(i)(500)394

**IMPORTANT**

Risk of spontaneous ignition: Oil-soaked cloths, abrasive dust, etc. can spontaneous ignite. Soak cloths etc. in water and dispose or keep in a fireproof container.