

Master Colour Oil provides colour and protection in one product. The oil penetrates the wood and ensures a hardwearing surface with high resistance to water and dirt. It is perfect for indoor use on all unfinished, new or newly-sanded surfaces in all wood species.

- **Resistant to dirt and fluids, e.g. water, coffee, tea and red wine**
- **Available in many different colours**
- **Gives the wood a beautiful, breathable surface**
- **Indoor climate labelled**



## Application area

For untreated, new or newly-sanded wooden surfaces.

## Work description

Preparation	Product, room and floor temperature must be between 15-30°C. Wood humidity must not exceed 12%. Ensure good ventilation during application and when drying. The wood must be newly sanded, use grit 100-120 for the final sanding. Vacuum thoroughly. Clean the wood with WOCA Intensive Wood Cleaner and leave it to dry for at least 8 hours before applying the oil.  Always remember to test on a less visible spot to check the compatibility of the surface with the product.
Final sanding	Grit 100-120
Treatment	Thoroughly shake the container of Master Colour Oil, both before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply the oil using a short-bristled paint roller (3-4 mm) in an even coat. Work in small areas of no more than 10 m <sup>2</sup> at a time. Leave the oil to soak in for 10-20 min. If the oil soaks quickly into the wood, apply more oil. Polish the oil into the wood until the surface appears saturated. Use a buffing machine with a beige pad for large areas and a polishing cloth/pad manually for small areas. Remove excess oil with dry, lint-free cotton cloths or pads until the surface no longer appears wet. Continue until the whole area has been polished and excess oil has been thoroughly removed. To ensure a good saturation the surface should be re-polished with 1 dl Master Colour Oil per 10 m <sup>2</sup> within 6-12 hours after the first application. The oil should be polished thoroughly, as described earlier.
Note	Do not expose the surface to water or clean it for the first 7 days while the oil is hardening. After 7 days the floor can be cleaned with WOCA Natural Soap, which gives the surface extra protection.

## Drying time

Drying time	12-24 hours at 20°C
Fully hard	5-7 days at 20°C and 55% humidity



## Technical data

---

Binder	Vegetable oil components
Density	0.90-0.95 g/ml
Solid content	Approx. 60 %
Shelf life	3 years
Application Temperature	15-30°C
Coverage (diluted)	Approx. 8-10 m <sup>2</sup> /L, depending on wood type and surface
Colours	11 colours
Cleaning of tools	With WOCA Solvent or turpentine.
Storage	+ 10-25°C. Keep out of reach of children. Must not be exposed to heat [e.g. sunlight]. Store frost-free.
VOC	This product contains max. 370 g VOC/l. Permitted value is 500 g VOC/l [cat.A/i].
Packaging	1 L - 2.5 L - 5 L
Migration test of non-desired materials	EN 71-3:2013
Authorisations	Danish Indoor Climate Labelling IBR: TVOC28/A+, GIS: Ö60

## Maintenance and related products

---

Weekly cleaning	Natural Soap, article no. 511010A
Monthly care	Oil Refreshing Soap, article no. 511210A
Re-oiling	Maintenance Oil, article no. 527310A/527410AA Maintenance Gel, article no. 527802A/527902A
Related products	Intensive Wood Cleaner, article no. 551525
Accessories	Paint Roller, 4 mm luv, article no. 88004 Paint roller handle, 25mm, article no. 599650 Telescopic rod, article no. 599651

## Contact

---

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*