



Linfolegno

FINISH FOR OIL TREATED WOODEN FLOORS FOR INTERIORS

COMPOSITION

Carnauba wax, beeswax, propolis, resin-wax emulsions, paraffin waxes, essences, water.

PROFILE

LINFOLEGNO is a resin-wax microemulsion with modified oils and natural wax, ideal for giving greater protection to parquet, (against substances of various kinds) to be used after pre-treating with oil or solid wax.

IMPORTANT: for regular cleaning, do not use alcohols, or acid, solvent or ammonia based-detergents.

INTENDED USE

LINFOLEGNO ensures fast and easy application on previously treated wooden surfaces. It gives parquet greater protection, with a soft and pearly effect, facilitating cleaning and maintenance. It can be used on various indoor wooden surfaces that have been treated previously with vegetable oils or hard wax.

IMPORTANT: before using the product always make sure that the manufacturing companies of the materials do not recommend against using it.

INSTRUCTIONS

Shake well before use. Always use at temperatures above +15°C. After at least 3-5 days from priming with Corolle, when the floor is clean and dry, apply **LINFOLEGNO** neutral with a damp cotton cloth and brush, applying a thin coat evenly, in the event of using the coloured versions we recommend applying by hand. After approximately 1-2 hours apply another coat, in the same manner. This is enough to ensure optimum floor protection. On large surfaces we recommend being very careful while applying the product, which must be applied approximately one metre at a time, in the direction of the wood grain, going from one side of the room to the other, in order not to overlap. **IMPORTANT:** The amount of days required for oil to harden always depend on the temperature, humidity and ventilation, therefore before applying **LINFOLEGNO** over the entire surface, always test it beforehand and check that it does not raise the wood grain. The protection given by the oil as a base coat is crucial, since **LINFOLEGNO** alone cannot ensure optimum protection.

PROS

- Develops a strong hydro-oil repellence.
- Facilitates the routine and special maintenance procedures
- Effective wear protection.
- High surface adhesion.
- Pleasantly scented
- It does not alter permeability to water vapour.
- It does not release harmful substances during application or after.
- Solvent-free.
- Simple normal use.
- It does not cause whitening even if water stays on the floor for several hours.

PROPERTIES

DILUTION: Ready for use.
DRYING: Approximately 1-2 hours (at 20°C) between applications. Maximum hardness after 24 hours.
YIELD: Approximately 25/35 sqm/l per coat.
HOW TO CLEAN EQUIPMENT: Wash with water.
STORAGE: Closed in the original packaging, in a cool place, away from frost and UV rays, it retains its properties for at least one year.
AVAILABLE VERSIONS: White, natural, gloss, satin-finish.
PACKAGING:
 12 1-litre bottles
 4 5-litre buckets
 2 10-litre buckets

CHEMICAL AND PHYSICAL CHARACTERISTICS

APPEARANCE: liquid
COLOUR: milky
ODOUR: pleasantly scented
ACTIVE INGREDIENTS: 22%
SOLUBILITY IN WATER: total.
SPECIFIC WEIGHT (20° C): 1.017 kg/l
PH (20° C): 8.5

HEALTH

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments. Hazard statements: EUH210 Safety data sheet available on request. No danger symbol is required on the label. It must nevertheless be kept out of the reach of children and must not be disposed of in drain water, in order to protect the environment. We nevertheless advise you to adopt good work practices.

Always run some test applications before applying it to the definitive surfaces

LIMITED WARRANTY - READ CAREFULLY

The information provided herein is provided in good faith and on the basis of careful research carried out by New Chemical Prevention. Nevertheless, since conditions and methods of use cannot be controlled by the company, this information does not replace preliminary tests, which are essential in guaranteeing full compliance and safety of the products to the specific application. Therefore New Chemical Prevention guarantees compliance only of the product with current sale specifications. Any compensation to the user or New Chemical Prevention liability are limited exclusively to reimbursing the purchase price or replacing any product that differs from its guaranteed specifications. New Chemical Prevention does not offer any explicit or implicit guarantee regarding product suitability and specific use for its commercial viability, unless the company provides a specific written guarantee of compliance for a specific use. New Chemical Prevention will not be held liable for accidental or indirect damage.

NEW CHEMICAL PREVENTION
 VIA MAESTRI DEL LAVORO, 10
 41034 FINALE EMILIA
 (MODENA) ITALY
 TEL+39 0535 91336
 FAX+39 0535 93763
 INFO@NEWCHEMICAL.IT
 WWW.NEWCHEMICAL.IT



NewChemical
 PREVENTION