

Oil Care may be used for the maintenance of all oiled wood surfaces and is especially suitable for the regular maintenance of oiled wood floors.

- **Simple application both manually and by machine**
- **Fast-drying**
- **Eco-friendly indoor environments**
- **For occasional maintenance**
- **IBR-certified**



Application area

For all oiled wood surfaces - whether they are finished with oxidative oil or UV oil [factory-oiled]. Oil Care Natural is suitable for dark wood species, whereas Oil Care White is used for lighter, possibly lyre treated wood such as pine, ash or oak, in order to preserve and enhance the light look.

Work description

Preparation	Clean the floor with 125 ml Intensive Wood Cleaner mixed into 5 liter water. Leave the floor to dry for at least 8 hours. The floor must be completely dry. Always remember to test on a less visible spot to check the compatibility of the surface with the product.
Treatment	Shake the container carefully. Polish in a thin layer of the Oil Care with a white pad, cotton cloth or use polishing machine for large surfaces. It is important that the Oil Care is carefully polished into the wood. Continue polishing until the wood appears saturated and the surface looks uniform. The floor should not appear wet and there should not be any excess oil left on the surface after polishing. Work in smaller areas one step at a time until the floor is finished.

Drying time

Light use	1-2 hours
Fully hard	24 hours
Recommendation	Do not expose the floor to water during hardening time – approx. 24 hours.



Technical data

Density	1
pH-value	7.5-8.5
Shelf life	36M
Coverage	30-40 m ² /L, depending on wood type and surface.
Colours	Natural and white.
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.
VOC	This product contains 1 g VOC/L. The limit value is 140 g VOC/L (cat. A/i).
Packaging	1 L

Maintenance and related products

Weekly cleaning	Natural Soap, #511025A
Monthly care	Oil Refreshing Soap, #511225A
Re-oiling	Maintenance Oil, #527325AA Maintenance Gel, #527802A
Related products	Intensive Wood Cleaner, #551525A
Application tools	Wool Pad, #596061 Polishing pad

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.